


### Description

The flexible 1/2" polyethylene dripline has large emitters regularly spaced in the line. With the dripline hidden about six inches below ground effluent is distributed slowly and uniformly, reducing ponding, even in difficult soils and hilly terrain.



WASTEFLOW is built to last. It is guaranteed to be trouble-free from root intrusion with built-in ROOTGUARD® protection, and the dripline wall is protected from organic growth with a bactericide lining. WASTEFLOW provides uniform distribution. The emitters have a Coefficient of variation (Cv) of less than .05.

Different flow rates, dripline diameters and emitter spacings can be special ordered.

Use 600 series compression adapters or lockslip fittings to connect the dripline to PVC pipe.

### ROOTGUARD® Protection

WASTEFLOW dripline features patented ROOTGUARD technology to prevent roots from clogging the emission points. The pre-emergent, Treflan®, is bound into WASTEFLOW emitters when they are molded to divert roots from growing into the emitter outlet. The system is guaranteed against root intrusion for 10 years.

### BACTERICIDE Protection

Geoshield™ is incorporated into the inner lining and emitters of WASTEFLOW dripline to prevent bacteria from forming and eliminates the need to scour the tubing. It is a tin based formula that defeats the energy system of microbial cells.

This means smaller pumps or larger zones can be used with WASTEFLOW dripline than unprotected dripline.

### PC vs. CLASSIC

Geoflow, Inc. offers WASTEFLOW dripline in both pressure compensating (WASTEFLOW PC) and non-compensating (WASTEFLOW Classic) models.


We recommend that WASTEFLOW PC be used when the advantages are of substantial economic value.

- a) Very long runs.
- b) Steep slopes. Systems should be designed for the dripline lateral to follow the contour. If this is possible, the extra cost of pressure regulators required for WASTEFLOW Classic would likely be less than the incremental cost of WASTEFLOW PC.
- c) Rolling terrain. If the difference in height from trough to peak exceeds six feet then WASTEFLOW PC should be used. Vacuum relief valves must be placed at the top of each rise.

WASTEFLOW PC and WASTEFLOW Classic can be interchanged to meet filter and zone flow requirements.

- 
- WASTEFLOW is manufactured under US Patents 5332160, 5116 414 and Foreign equivalents.
  - Geoshield™ is a registered trademark of A.I. Innovations.
  - WASTEFLOW is a registered trademark of A.I. Innovation
  - TREFLAN is a registered trademark of Dow Agro Chemicals.

# WASTEFLOW Classic



## Available in 2 standard models

WF16-4-24- WASTEFLOW Classic 24"/1.3gph

WF16-4-12- WASTEFLOW Classic 12"/1.3gph

Alternate flow rates, diameters and spacing available upon request

## Flow Rate vs. Pressure

Pressure psi	Head ft.	ALL WASTEFLOW Classic Dripline
10 psi	23.10 ft.	.90 gph
15 psi	34.65 ft.	1.13 gph
20 psi	46.20 ft.	1.30 gph
25 psi	57.75 ft.	1.47 gph
30 psi	69.30 ft.	1.62 gph
35 psi	80.85 ft.	1.76 gph
40 psi	92.40 ft.	1.82 gph
45 psi	103.95 ft.	1.89 gph

## WASTEFLOW Classic Specification

The dripline shall consist of nominal sized one-half inch linear low density polyethylene tubing, with turbulent flow, drip emitters bonded to the inside wall. The drip emitter flow passage shall be 0.053" x 0.053" square. The tubing shall have an outside diameter (O.D.) of approximately .64-inches and an inside diameter (I.D.) of approximately .55-inches. The tubing shall consist of three layers; the inside layer shall be Geosheid protection, the middle layer shall be black and the outside layer shall be purple striped for easy identification. The dripline shall have emitters regularly spaced 24" (or 12") apart. The turbulent flow emitters shall be molded from virgin polyethylene resin. The turbulent flow emitters shall have nominal discharge rates of 1.3 gallons per hour at 20 psi. The emitters shall be impregnated with Treflan® to inhibit root intrusion for a minimum period of ten years and shall be guaranteed by the manufacturer to inhibit root intrusion for this period. WASTEFLOW Classic dripline shall be Geoflow model number WF16-4-24 (or WF16-4-12).

## Maximum Length of Run vs. Pressure


Flow variation +/- 5%

Pressure psi	Head ft.	Emitter Spacing		
		24"	18"	12"
10 psi	23.10 ft.	170'	165'	100'
15 psi	34.65 ft.	170'	165'	100'
20 psi	46.20 ft.	170'	165'	100'
25 psi	57.75 ft.	170'	165'	100'
30 psi	69.30 ft.	170'	165'	100'
35 psi	80.85 ft.	170'	165'	100'
40 psi	92.40 ft.	170'	165'	100'
45 psi	103.95 ft.	170'	165'	100'


Kd=0.9 Cv < .05

## Wasteflow Classic 1 gph

Pressure Loss vs. Length of Run



## WASTEFLOW PC 1/2 gph



### Standard products:

WFPC16-2-24 WASTEFLOW PC 24"/.53gph

WFPC16-2-18 WASTEFLOW PC 18"/.53gph

WFPC16-2-12 WASTEFLOW PC 12"/.53gph

Alternative spacing, flow rates and diameters available upon request

### Flow Rate vs. Pressure

Pressure	Head	ALL WASTEFLOW PC 1/2 gph dripline
7-60 psi	16-139 ft.	0.53 gph

### Maximum Length of Run vs. Pressure

Allows a minimum of 10 psi in the line.


Recommended operatin pressure 10-45 psi

Pressure psi	Head ft.	Emitter Spacing			
		6"	12"	18"	24"
10 psi	23.10 ft.				
15 psi	34.65 ft.		174'	260'	321'
20 psi	46.20 ft.	120'	229'	330'	424'
25 psi	57.75 ft.		260'	377'	478'
30 psi	69.30 ft.	150'	288'	415'	535'
35 psi	80.85 ft.		313'	448'	576'
40 psi	92.40 ft.	172'	330'	475'	612'
45 psi	103.95 ft.		354'	501'	651'
50 psi	115.5 ft.		363'	523'	675'
55 psi	127.05 ft.		377'	544'	700'
60 psi	138.6 ft.		403'	563'	727'


### WASTEFLOW PC 1/2 gph PC Specification

The dripline shall consist of nominal sized one-half inch linear low density polyethylene tubing, with turbulent flow, drip emitters bonded to the inside wall. The drip emitter flow passage shall be 0.032" x 0.045" square. The tubing shall have an outside diameter (O.D.) of approximately .64-inches and an inside diameter (I.D.) of approximately .55-inches. The tubing shall consist of three layers; the inside layer shall be a Geoshield protection, the middle layer shall be black and the outside layer shall be purple striped for easy identification. The dripline shall have emitters regularly spaced 24" (or 18" or 12") apart. The pressure compensating emitters shall be molded from virgin polyethylene resin with a silicone rubber diaphragm. The pressure compensating emitters shall have nominal discharge rates of 0.53 gallons per hour. The emitters shall be impregnated with Treflan® to inhibit root intrusion for a minimum period of ten years and shall be guaranteed by the manufacturer to inhibit root intrusion for this period. 0.53 gph WASTEFLOW PC pressure compensating dripline shall be Geoflow model number WFPC16-2-24 (or WFPC16-2-18 or WFPC16-2-12) .

### Wasteflow PC 1/2 gph



## WASTEFLOW PC 1 gph



### Flow Rate vs. Pressure

Pressure	Head	ALL WASTEFLOW PC 1 gph dripline
7-60 psi	16-139 ft.	1.02 gph

### Maximum Length of Run vs. Pressure

Allows a minimum of 10 psi in the line.

Recommended operatin pressure 10-45 psi

Pressure		Emitter Spacing			
psi	ft.	6"	12"	18"	24"
10 psi	23.10 ft.	50'	95'	140'	175'
15 psi	34.65 ft.	63'	115'	172'	211'
20 psi	46.20 ft.	74'	146'	210'	265'
25 psi	57.75 ft.	88'	171'	242'	315'
30 psi	69.30 ft.	94'	180'	266'	335'
35 psi	80.85 ft.	103'	199'	287'	379'
40 psi	92.40 ft.	110'	211'	305'	385'
45 psi	103.95 ft.	116'	222'	321'	429'
50 psi	115.5 ft.		232'	334'	431'
55 psi	127.05 ft.		240'	347'	449'
60 psi	138.6 ft.		249'	360'	465'

### Standard Products:

WFPC16-4-24 WASTEFLOW PC 24"/1.02 gph

WFPC16-4-18 WASTEFLOW PC 18"/1.02 gph


WFPC16-4-12 WASTEFLOW PC 12"/1.02 gph

Alternative spacing, flow rates and diameters available upon request

### WASTEFLOW PC 1 gph PC Specification

The dripline shall consist of nominal sized one-half inch linear low density polyethylene tubing, with turbulent flow, drip emitters bonded to the inside wall. The drip emitter flow passage shall be 0.032" x 0.045" square. The tubing shall have an outside diameter (O.D.) of approximately .64-inches and an inside diameter (I.D.) of approximately .55-inches. The tubing shall consist of three layers; the inside layer shall be Geoshield protection, the middle layer shall be black and the outside layer shall be purple striped for easy identification. The dripline shall have emitters regularly spaced 24" (or 18" or 12") apart. The pressure compensating emitters shall be molded from virgin polyethylene resin with a silicone rubber diaphragm. The pressure compensating emitters shall have nominal discharge rates of 1.02 gallons per hour. The emitters shall be impregnated with Treflan® to inhibit root intrusion for a minimum period of ten years and shall be guaranteed by the manufacturer to inhibit root intrusion for this period. 1.02 gph WASTEFLOW PC pressure compensating dripline shall be Geoflow model number WFPC16-4-24 (or WFPC16-4-18 or WFPC16-4-12) .

### Wasteflow FC 1 gph



Geoflow, Inc. 415-927-6000/800-828-3388 Fax: 415-927-0120 www.geoflow.com

Product sheet- WASTEFLOW Dripline-07E04